

**SLIMLINK**

The everywhere light.

INTRODUCING THE MOST  
VERSATILE LIGHTING SYSTEM EVER.



WHEN YOU NEED TO SEE THE LIGHT,  
NOT THE FIXTURE.

**SPECIALTY LIGHTING**  
A DIVISION OF JJI LIGHTING GROUP, INC.

## SLIMLINK FLUORESCENT FIXTURES

- ALUMINUM REFLECTOR
- BUILT-IN ON/OFF SWITCH
- ACRYLIC PRISMATIC DIFFUSER
- STANDARD 6' POWER CORD




### FIXTURE INCLUDES

- DIFFUSER
- 6' CORD
- ON/OFF ROCKER SWITCH
- LAMPED-T4
- ELECTRONIC BALLAST
- FINISH - WHITE OR BLACK
- CONTINUOUS LTG - 250W
- LAMP LIFE - 5000 HOURS

Direct linkable system permits easy connection for continuous lighting.



Connector Cord enables linking up to 10 units maximum or 250 watts .



Mounting Clips and hardware.



Available in white or black.



## ULTRA SLIM DESIGN

3/4" WIDE, 1 11/16" HIGH. 4 LENGTHS AVAILABLE. USES T4 LAMP. AVAILABLE IN WHITE OR BLACK.


MAY BE USED AS SINGLE FIXTURE WITH POWER CORD OR BUTT-LINKED TOGETHER TO FORM A STRIP — 250W MAX. MAY BE DAISY-CHAINED BY USING CONNECTING CABLE. 10 UNIT MAXIMUM IN LINE.

### APPLICATIONS

- UNDER CABINET
- CABINETS AND BOOK CASES
- OFFICE FURNITURE
- COMPUTER WORK STATION
- RETAIL DISPLAY
- KITCHEN & BATH
- UNDERSURFACE
- TASK LIGHTING
- CLOSETS
- SUITABLE FOR INDOOR USE ONLY

## SPECIALTY LIGHTING

639 Washburn Switch Rd  
Shelby, NC 28150  
704-482-3416




90° POWER CORD



90° PIGTAIL POWER CORD

HARDWIRE BOX WITH SWITCH



### SLIMLINK CATALOG NUMBERS

- SLF106CWWH 10"6W CW LAMP WHITE
- SLF1410CWWH 14"10W CW LAMP WHITE
- SLF2016CWWH 20"16W CW LAMP WHITE
- SLF2320CWWH 23"20W CW LAMP WHITE

- CW = cool white      WH = white
- WW = warm white    BK = black

### CONNECTING CABLES

- SLFCC6 6"
- SLFCC12 12"
- SLFCC18 18"
- SLFCC24 24"
- SLFCC36 36"
- SLFCC48 48"
- SLFCC72 72"

Consult Factory Custom Lengths

### POWER CORDS

- SLFPC6 6'
- SLFPC12 12'
- SLFPC6 6' 90°
- SLFPC690HW 6' 90° Hardwire (pigtail)

### HARDWIRE BOXES

- SLFHW HARDWIRE BOX
- SLFHWS HARDWIRE BOX WITH SWITCH

### LAMPS

- SLF6CW SLF10CW SLF16CW SLF20CW
- SLF6WW SLF10WW SLF16WW SLF20WW

### TECHNICAL INFORMATION

	SLF106	SLF1410	SLF2016	SLF2320
FIXTURE LENGTH	10 3/4"	15 1/2"	20 1/2"	24 7/16"
FIXTURE WIDTH	3/4"	3/4"	3/4"	3/4"
FIXTURE HEIGHT WITH DIFFUSER	1 11/16"	1 11/16"	1 11/16"	1 11/16"
TUBE LENGTH	8 5/8"	13 3/8"	18 3/8"	22 5/16"
TUBE DIAMETER	T4(1/2")	T4(1/2")	T4(1/2")	T4(1/2")
WATTS	6	10	16	20
LUMENS	265	450	860	1000
LUMENS W/O DIFFUSER	300	500	880	1200
CURRENT	0.14A	0.18A	0.20A	0.20A
IN-RUSH CURRENT	LESS THAN 5 AMP			
SURFACE TEMPERATURE	38°C	40°C	41°C	41°C
CRI	>82			
VOLTAGE	120V			
FREQUENCY	60 Hz			
MAXIMUM WATTS IN LINE	250 WATTS 10 UNIT MAXIMUM IN LINE			