



Project:	Type:
Item. No.	
Location:	
Notes:	

DPC2




designer power communication series

standard features

- Electrical rating: 120V, 60 Hz
- Power cord: 10' 14/3 SJT (black) with right angle plug
- Finish: Black
- Construction: metal
- Tamper-resistant outlets (meets NEC requirements)
- Powered USB (A-style) – compatible with USB 2.0 & 3.0 devices
- Circuit breaker
- Installation method: 2 mounting brackets (when installed, no exposed hardware), adjustable for different panel thickness (min 1/2" – max 1 1/4")
- Recess mount only – see drawing for route size
- UL & cUL

options

- Hospital grade outlets and power cord
- Surge suppression (SS)
- Female connector (FC)
- The following options are available - minimums may apply
 - Rockerswitch (RKS), or switch/breaker combo (SW)
 - Non-powered pass-thru telephone, data, HDMI, etc.
 - Finishes below, other than standard black
 - Contact factory for custom options



ordering information (example: DPC2-A1-D1-1-BK)

product	model	module 1 module type & color	module 2 module type & color	power cord	finish	surge	options
DPC	2	A1	D1	1	BK		
DPC	2 2 modules	A-J 15A O-W 20A color options	A-J 15A O-W 20A color options	1 10' 14/3 SJT (standard with 15A modules)	BK black (standard) IV ivory LA light almond	blank none SS surge	blank none FC female connector SW switch/breaker combo RKS rocker switch 5E RJ45 data 6 RJ45 data USB non-powered pass-thru
		1 black 2 ivory 3 light almond 4 nickel* 5 white 6 grey* 7 red*	1 black 2 ivory 3 light almond 4 nickel* 5 white 6 grey* 7 red*	2 10' 14/3 SJT-HG 3 10' 12/3 SJT-20A (standard with 20A modules)	NK nickel WH white		
		*not available for all module types		4 10' 12/3 SJT-HG			

module selection

15A modules – for use with 14/3 power cord



A
two outlets



C
two outlets
two charging
USBs
(3.1A total
charging
capacity)



H
Hospital Grade
two outlets



J
Hospital Grade
two outlets
two charging
USBs
(3.1A total
charging
capacity)

20A modules – for use with 12/3 power cord



O
two outlets



Q
two outlets
two charging
USBs
(3.1A total
charging
capacity)



U
Hospital Grade
two outlets



W
Hospital Grade
two outlets
two charging
USBs
(3.1A total
charging
capacity)

color options for modules



1 = black
(standard)



2 = ivory



3 = light almond



4 = nickel*



5 = white



6 = grey*



7 = red*

*not available for all modules