



Project: _____ Type: _____

Item. No. _____

Location: _____


Notes: _____

RD60

recessed downlight - trimless

standard features

- Electrical rating: 120V, 60Hz
- LED integrated technology (non-replaceable lamp)
- Initial lumens: 760
- Beam angle: 120°
- Power Cord: 18/2 SPT-2 (black)
- Finish: Painted: black (BK), white (WH)
Plated: antique brass (AB), brushed nickel (BN), polished brass (PB), polished chrome (PC)
- Construction: steel
- Installation method: adjustable mounting ring pre-installed 7/8" from canister opening. Installation hole diameter 3 3/8".
- Height: 2 7/8"
- Diameter: 3 1/4"
- Compatible with Specialty Lighting PH3121 (on/off switch) and PD6113 (full range rotary dimmer)
- 8 watt
- 5 year warranty
- Link up to 50 fixtures maximum
- UL and cUL



ordering information

product	color temp	wiring	connector style	finish	installation method
RD60	827	2	S	PB	R
	827 2700K extra warm 830 3000K warm	1 10' power cord with roll switch located 5' from plug 2 10' power cord with roll switch located 5' from plug & 30" extension with female connector 3 30" male & female extensions 4 30" male extension	S standard T t-shaped	AB Antique Brass BK Black BN Brushed Nickel PB Polished Brass PC Polished Chrome WH White (minimums may apply)	R ring mount