




Project:	Type:
Item. No.	
Location:	
Notes:	

RD60

recessed downlight - trimless

standard features

- Electrical rating: 120V, 60Hz
- LED integrated technology (non-replaceable lamp)
- Initial lumens: 760
- Beam angle: 120°
- Power Cord: 18/2 SPT-2 (black)
- Finish: Painted: black (BK), white (WH)
Plated: antique brass (AB), brushed nickel (BN),
polished brass (PB), polished chrome (PC)
- Construction: steel
- Installation method: adjustable mounting ring pre-installed $\frac{7}{8}$ " from canister opening. Installation hole diameter $3\frac{3}{8}$ ".
- Height: $2\frac{7}{8}$ "
- Diameter: $3\frac{1}{4}$ "
- Compatible with Specialty Lighting PH3121 (on/off switch) and PD6113 (full range rotary dimmer)
- 8 watt
- 5 year warranty
- Link up to 50 fixtures maximum
- UL and cUL



ordering information

product	color temp	wiring	connector style	finish	installation method
RD60	827	2	S	PB	R
	827 2700K extra warm 830 3000K warm	1 10' power cord with roll switch located 5' from plug 2 10' power cord with roll switch located 5' from plug & 30" extension with female connector 3 30" male & female extensions 4 30" male extension	S standard T t-shaped	AB Antique Brass BK Black BN Brushed Nickel PB Polished Brass PC Polished Chrome WH White (minimums may apply)	R ring mount