Spec Sheet ptl series

Type:



ptl series

standard features

- Electrical rating: 120V, 60Hz
- Lamp: T8, fluorescent (included)
- Ballast: electronic
- Power cord: 9' 16/3 SJT (black)
- Finish: black powder coat
- Construction: heavy gauge steel channels
- Installation method: screw holes located in fixture body
- Available in a variety of lengths
- Cord management guides standard
- Centrally located on/off switch
- Clear prismatic lens
- UL and cUL



Power cord locations (B-D): C is standard specify alternate power cord location on specification sheet



ordering information

item number	catalog number	length	finish	lamp
4200-0100	PTL18-BK	18"	black	F15T8
4200-0200	PTL24-BK	24"	black	F17T8
4200-0220	PTL48-BK	48"	black	F32T8

accessories

item number	catalog number	sets	finish	description
350-979	PTL-MBR	set of 2	black	mounting bars
350-981	PTL-MBKT	set of 2	black	mounting brackets

replacement lamps

item number	catalog number	description
485-385	F15T8/4100K	15 watts, T8
485-362	F17T8/3500K	17 watts, T8
485-355.5	F25T8/3500K	25 watts, T8
485-357	F32T8/3500K	32 watts, T8
485-361	F40T8/3500K	40 watts, T8

See Lamps spec sheet for additional options.

task lights

options

Project:

Item. No.

Location:

Notes:

- Ballast for other voltage requirements
- Romex connector for hardwiring by an electrician
- Female connecting cables to link adjacent fixtures
- Grounded convenience outlet
- Switches and sensors
- Batwing lens
- Other finishes
- Mounting bars and brackets
- Lamps for other color temperatures
- Contact factory for custom options

