



Project: \_\_\_\_\_ Type: \_\_\_\_\_

Item. No. \_\_\_\_\_

Location: \_\_\_\_\_

Notes: \_\_\_\_\_

# lamps

## ordering information



T10 (inter) *incandescent 120 volt*

bulb	base	watts	item number	description	rated avg life (hrs)	lumens	box qty
T6	med	15	398-320	15T6/C - clear	2000	100	25
T10	med	15	398-340	15T10/C - clear	2500	120	25
T10	med	25	398-520	torpedo tip 25ETC/32	1500	200	25
T10	med	25	398-840	25T10/C - clear	1000	260	25
T10	med	25	398-850	25T10/F - frosted	1000	255	25
R14	med	40	398-1370	40R14	1500	250	25
R14	inter	40	398-1320	40R14N	1500	250	24
S11	inter	40	398-1440	40S11N/C - clear	500	420	25
S11	inter	40	398-1480	40S11N/F - frosted	500	420	25
R20	inter	50	398-1580	50R20	2000	400	25



T10 (med)



T10 (ETC)



R14

## halogen 120 volt

bulb	base	watts	item number	description	rated avg life (hrs)	lumens	box qty
T4	G8	20	398-111	120V G8 20W (xenon)	2000	N/A	25
T4	G8	25	251-52	120V G8 25W	2000	200	25
HR	med	35	398-995	35HR16	1500	385	25
HR	inter	35	398-970	35HR16N	1500	385	20
PAR20	med	50	485-175	50PAR20	2500	570	36



S11 (inter)



R20

## halogen 12 volt

bulb	base	watts	item number	description	rated avg life (hrs)	lumens	box qty
T3	G4	10	398-95	12V G4 10W	2000	140	25
T3	G4	10	398-90	12V G4 10W (xenon)	2000	140	25
T3	G4	20	398-375	12V G4 20W	2000	350	25
T3	G4	20	398-380	12V G4 20W (xenon)	2000	350	25



HR



PAR20

## MR-16 12 volt (halogen)

bulb	base	watts	item number	description	rated avg life (hrs)	lumens	box qty
MR-16	GU5.3	10	398-350	10MR1612V	1200	10	10
MR-16	GU5.3	20	398-373	20MR1612V	5000	10	10
MR-16	GU10	35	398-365	35MR1612V-Flood	2000	10	10
MR-16	GU5.3	35	485-132	Q35MR16C/CG40	5000	10	10
MR-16	GU5.3	37	398-372	Q37MR16/HIR/CG25	5000	10	10
MR-16	GU5.3	50	398-400	50MR1612V	5000	10	10
MR-16	GU5.3	50	485-133	50MR1612V-Flood	5000	10	10



halogen 12v



MR-16

# lamps

## fluorescent T5 (5/8" diameter)



T5

bulb	base	watts	item number	description	nominal length	rated avg life (hrs)	initial lumens	box qty
T5	bi-pin	6	485-230	F6T5/CW	9"	7,500	325	10
T5	bi-pin	6	485-236	F6T5/WW	9"	7,500	325	10
T5	bi-pin	8	485-240	F8T5/CW	12"	7,500	400	10
T5	bi-pin	8	485-260	F8T5/WW	12"	7,500	450	10
T5	bi-pin	13	485-265	F13T5/CW	21"	7,500	860	10
T5	bi-pin	13	485-250	F13T5/WW	21"	7,500	1000	10
T5	bi-pin	14	485-262	F14T5/CW	22"	20,000	1350	40
T5	bi-pin	14	485-255	F14T5/WW	22"	20,000	1350	40
T5	bi-pin	21	485-266	F21T5/CW	34"	20,000	2100	40
T5	bi-pin	21	485-267	F21T5/WW	34"	20,000	2100	40
T5	bi-pin	28	485-268	F28T5/CW	46"	20,000	2900	40
T5	bi-pin	28	485-275	F28T5/WW	46"	20,000	2900	40
T5	bi-pin	35	485-269	F35T5/CW	58"	20,000	3650	40
T5	bi-pin	35	485-278	F35T5/WW	58"	20,000	3650	40

## fluorescent T8 (1" diameter)



T8

bulb	base	watts	item number	description	nominal length	rated avg life (hrs)	initial lumens	box qty
T8	bi-pin	15	485-385	F15T8/CW	18"	7,500	870	25
T8	bi-pin	15	485-290	F15T8/WW	18"	7,500	1000	25
T8	bi-pin	17	485-355	F17T8/CW	24"	24,000	1350	25
T8	bi-pin	17	485-354.5	F17T8/N	24"	24,000	1350	25
T8	bi-pin	17	485-353	F17T8/WW	24"	24,000	1350	25
T8	bi-pin	25	485-356	F25T8/CW	36"	24,000	2150	25
T8	bi-pin	25	485-355.5	F25T8/N	36"	24,000	2150	25
T8	bi-pin	25	485-352	F25T8/WW	36"	24,000	2150	25
T8	bi-pin	32	485-358	F32T8/CW	48"	24,000	2850	25
T8	bi-pin	32	485-357	F32T8/N	48"	24,000	2850	25
T8	bi-pin	32	485-365	F32T8/WW	48"	24,000	2850	25
T8	bi-pin	40	485-359	F40T8/CW	60"	24,000	3600	25
T8	bi-pin	40	485-361	F40T8/N	60"	24,000	3600	25
T8	bi-pin	40	485-364	F40T8/WW	60"	24,000	3600	25

## LED



LED MR-16



LED PAR20

bulb	base	watts	item number	description	rated avg life (hrs)	lumens	box qty
MR-16	GU5.3	3	398-03	3WMR16,12V, LED, WW	25,000	170	10
PAR20	med	5	398-20	5WPAR20,120V, LED, CW	25,000	500	10

Contact factory for other lamp options.